

AMENDMENTS TO THE CLAIMS:

The listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF THE CLAIMS

1. (Currently Amended) A method for applying individualized calibrated tone-reproduction curves to enable printing of image data, comprising ~~the steps of:~~

- (a) providing a plurality of calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct media type;
- (b) determining a media type to be used in printing the image data;
- (c) selecting a calibrated tone-reproduction curve based on the determined media type; and
- (d) applying the selected calibrated tone-reproduction curve to print the image data; and
- (e) generate a map to link a stored tone-reproduction curve to a media type, the stored tone-reproduction curve being capable of being mapped to more than one media type.

2. (Currently Amended) The method as claimed in claim 1, further comprising ~~the step of:~~

- (e) determining a halftone to be used in printing the image data;
- said step (a) providing a plurality of stored calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;
- said step (c) selecting a calibrated tone-reproduction curve based on the determined media type and determined halftone type combination.

3. (Currently Amended) The method as claimed in claim 1, further comprising ~~the steps of:~~

- (e) performing a plurality of calibration operations, each calibration operation using a distinct media type;
- (f) generating a tone-reproduction curve for each media type; and
- (g) storing the generated the tone-reproduction curves;

said step (a) providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type.

4. (Currently Amended) The method as claimed in claim 1, further comprising the steps of:

(e) performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

(f) generating a tone-reproduction curve for each media type and halftone type combination;

(g) storing the generated the tone-reproduction curves; and

(h) determining a halftone to be used in printing the image data;

said step (a) providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type and halftone type combination;

said step (c) selecting a calibrated tone-reproduction curve based on the determined media type and determined halftone type.

5. (Currently Amended) The method as claimed in claim 1, further comprising the steps of:

(e) performing a plurality of calibration operations, each calibration operation using a distinct media type;

(f) generating a tone-reproduction curve for each media type calibration;

(g) comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics,

(h) selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media types that generated the tone-reproduction curve having similar characteristics;

(i) storing selected and non-grouped tone-reproduction curves; and

~~(j) generating a map to link a stored tone-reproduction curve to a media type, a stored tone-reproduction curve being capable of being mapped to more than one media type;~~

said step (a) providing a plurality of stored calibrated tone-reproduction

curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type;

6. (Currently Amended) The method as claimed in claim 1, further comprising ~~the steps of:~~

(e) performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

(f) generating a tone-reproduction curve for each media type and halftone type combination calibration;

(g) comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

(h) selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media type and halftone type combinations that generated the tone-reproduction curve having similar characteristics;

(i) storing selected and non-grouped tone-reproduction curves; and

(j) ~~generating a map to link a stored tone-reproduction curve to a media type and halftone type combination, a stored tone-reproduction curve being capable of being mapped to more than one media type and halftone type combination; and~~

(k) determining a halftone to be used in printing the image data;

said step (a) providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type and halftone type combination;

said step (c) selecting a calibrated tone-reproduction curve based on the determined media type and determined halftone type.

7. (Currently Amended) The method as claimed in claim 1, further comprising ~~the step of:~~

printing of image data on a xerographic printing device using the selected calibrated tone-reproduction curve.

8. (Currently Amended) A system for applying individualized calibrated tone-reproduction curves to enable printing of image data, comprising:

a storage device to store and provide a plurality of calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

an input device to select a media type to be used in printing the image data and to select a halftone to be used in printing the image data; and

a processor to select a calibrated tone-reproduction curve based on the selected media type and determined halftone type and to apply the selected calibrated tone-reproduction curve to print the image data; and

a said calibration means generating a map to link a stored tone-reproduction curve to a media type, a stored tone-reproduction curve being capable of being mapped to more than one media type.

9. (Previously Presented) The system as claimed in claim 8, further comprising: a xerographic printing device using the selected calibrated tone-reproduction curve to print image data.

10. (Previously Presented) The system as claimed in claim 8, wherein: said input device selects a halftone to be used in printing the image data; said storage device provides a plurality of calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination; said processor selects a calibrated tone-reproduction curve based on the selected media type and selected halftone type.

11. (Previously Presented) The system as claimed in claim 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type;

said storage device storing the generated the tone-reproduction curves and providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type.

12. (Previously Presented) The system as claimed in claim 8, further

comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type; said input device selecting a halftone to be used in printing the image data;

said storage device storing the generated the tone-reproduction curves and providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and selected halftone type.

13. (Currently Amended) The system as claimed in claim 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media types that generated the tone-reproduction curve having similar characteristics;

said storage device storing selected and non-grouped tone-reproduction curves;

~~said calibration means generating a map to link a stored tone reproduction curve to a media type, a stored tone reproduction curve being capable of being mapped to more than one media type;~~

said storage device providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type.

14. (Previously Presented) The system as claimed in claim 8, further

comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

said calibration means generating a tone-reproduction curve for each media type and halftone type combination calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media type and halftone type combinations that generated the tone-reproduction curve having similar characteristics;

said storage device storing selected and non-grouped tone-reproduction curves;

said calibration means generating a map to link a stored tone-reproduction curve to a media type and halftone type combination, a stored tone-reproduction curve being capable of being mapped to more than one media type and halftone type combination;

and said input device selecting a halftone to be used in printing the image data;

said storage device providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type and halftone type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and selected halftone type.

15. (Previously Presented) The system as claimed in claim 9, further comprising:

an auto-segmentation circuit to determine a halftone to be used in printing the image data;

said storage device providing a plurality of calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said processor selecting a calibrated tone-reproduction curve based on the

selected media type and determined halftone type.

16. (Previously Presented) The system as claimed in claim 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type; and

an auto-segmentation circuit to determine a halftone to be used in printing the image data;

said storage device storing the generated the tone-reproduction curves and providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and determined halftone type.

17. (Previously Presented) The system as claimed in claim 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

said calibration means generating a tone-reproduction curve for each media type and halftone type combination calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media type and halftone type combinations that generated the tone-reproduction curve having similar characteristics;

said storage device storing selected and non-grouped tone-reproduction curves;

said calibration means generating a map to link a stored tone-reproduction curve to a media type and halftone type combination, a stored tone-reproduction

curve being capable of being mapped to more than one media type and halftone type combination;

and an auto-segmentation circuit to determine a halftone to be used in printing the image data;

said storage device providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type and halftone type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and determined halftone type.

18. (Currently Amended) A system for applying individualized calibrated tone-reproduction curves to enable printing of image data, comprising:

storage means for storing and providing a plurality of calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

first means for determining a media type to be used in printing the image data;

second means for determining a halftone to be used in printing the image data; and

third means for selecting a calibrated tone-reproduction curve based on the determined media type and determined halftone type and applying the selected calibrated tone-reproduction curve to print the image data; and

a calibration means generating a map to link a stored tone-reproduction curve to a media type and halftone type combination, the stored tone-reproduction curve being capable of being mapped to more than one media type and halftone type combination;

19. (Original) The system as claimed in claim 18, further comprising:

a xerographic printing device using the selected calibrated tone-reproduction curve to print image data.

20. (Original) The system as claimed in claim 18, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type;

said storage means storing the generated the tone-reproduction curves and providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said third means selecting a calibrated tone-reproduction curve based on the determined media type and determined halftone type.

21. (Currently Amended) The system as claimed in claim 18, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

said calibration means generating a tone-reproduction curve for each media type and halftone type combination calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media type and halftone type combinations that generated the tone-reproduction curve having similar characteristics;

said storage means storing selected and non-grouped tone-reproduction curves;

~~said calibration means generating a map to link a stored tone reproduction curve to a media type and halftone type combination, a stored tone reproduction curve being capable of being mapped to more than one media type and halftone type combination;~~

and said storage means providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type and halftone type combination;

said third means selecting a calibrated tone-reproduction curve based on the determined media type and determined halftone type.